

# Full-range audio, simple ceiling installation



Topcat's hybrid speaker design delivers superior audio quality of voice and multimedia.

All-in-one design combined with wireless audio integration makes installation simple and cost effective for both new construction and existing classrooms.

Combined with Flexmike, Topcat delivers the teacher's voice clearly throughout the classroom.

- **Wireless multimedia integration**
- **Seamless design, in-ceiling installation**
- **Add a second microphone for student sharing**

## Instructional audio creates better access to learning...

When students hear every word, valuable teaching time is more productive and effective for all

# 43%

Less off-task behavior<sup>1</sup>

1 Clackamas County, OR, 2002

# 72%

Fewer teacher redirections

# 13%

Less teacher absenteeism

## ...and overcomes physical barriers to listening.



CLASSROOM NOISE



DISTANCE




MASKS



HEARING LOSS

### WHOLE CLASS SOLUTIONS

#### CEILING-MOUNTED



Topcat

#### INSTALLED AUDIO SYSTEMS



975


#### PLUG & PLAY, PORTABLE



Redcat

## Ceiling-mounted Instructional Audio

Topcat seamlessly lays into the ceiling to deliver crystal clear audio for the whole class. The wireless Media Connector enables audio integration without long cable runs, while Activate and Pods can be added to facilitate small group collaborative learning.



## Specifications

|  |  |
|--|--|
| <b>Wireless Communication</b>            | Access Technology (1.9 GHz)  |
| <b>Wireless Transmission Range</b>       | Up to 200 ft. (60m) open field   |
| <b>Integrated Hybrid Speaker System</b>  | Exciter technology sound panel and low frequency cone driver                                     |
| <b>Power Output</b>                      | 20 watts RMS   |
| <b>Frequency Response</b>                | 60 Hz - 18 kHz (-10dB)   |
| <b>Power Input</b>                       | AC Mains: 100-240V ~ 50/60Hz 1.5A<br>DC: 24V/2.5A  |
| <b>Audio Inputs</b>                      | One 3.5mm input, one SPID/F coaxial digital input  |
| <b>Digital Audio Outputs</b>             | One SPID/F digital output for speaker expansion  |
| <b>Life Safety Interface Connections</b> | Inputs: PageFirst (25/70V page mute, relay mute)<br>Output: Contact Closure (triggered from mic) |
| <b>Dimensions (W x D x H)</b>            | 24" x 12" x 3.7" (595 x 295 x 94mm)  |
| <b>Weight</b>                            | 13.5 lbs (6.1 kg)  |



- 1 Topcat**  
 COMBINES A CONE SPEAKER FOR MULTIMEDIA, AND A FLAT-PANEL SPEAKER FOR VOICES
- 2 Flexmike**  
 LIGHTWEIGHT, PENDANT-STYLE MIC
- Charger**  
 CHARGES BOTH FLEXMIKE AND SHAREMIKE

## Popular Options

- 3 Multimedia Integration**  
 MEDIA CONNECTOR FOR WIRELESS INTEGRATION
  - 4 Small Group Learning**  
 ACTIVATE SYSTEM WITH PODS
  - Student Sharing**  
 SHAREMIKE
- Systems can be configured with either Media Connector or Activate (not both)

## Life Safety Integrations

Built-in integrations to third-party safety systems enhances classroom security.

- 
**Paging Priority**  
 MUTES INSTRUCTIONAL AUDIO SYSTEM
- 
**Fire Alarms**  
 MUTES INSTRUCTIONAL AUDIO SYSTEM
- 
**Alert Notifications**  
 ACTIVATE ALERT WITH FLEXMIKE